




Light Distribution (both): 100:0(100% For Eyepiece);
80:20 (80% For Trinocular Head And 20% For Eyepiece)



Oversize View Field Eyepiece, View Field
Up To 22mm For Comfortable Observation



Dark Field Objective, Make
Observation In Dark & Bright Field



Oversized Three-layer Working
Stage, More Choice For Samples.



Analyzer & Polarizer for
Simple Polarizing Observation

- New research and new development
- Combination with bright field, dark field, polarizing observation etc. Widely used in metal, mineral, electronic field.

Item	Specification	RIM-10	RIM-10D
Eyepiece	WF10× / 22mm (adjustable)	•	•
	WF10× / 22mm (adjustable, reticule 0.1mm)	•	•
Metallurgical LWD Infinity Plan Objectives	LPL 5× / 0.13 W.D.=24.23mm	•	○
	LPL 10× / 0.25 W.D.= 18.48mm	•	○
	LPL 20× / 0.40 W.D.= 8.35mm	•	○
	LPL 50× / 0.70(S) W.D.= 1.95mm	•	○
	LPL 40× / 0.65 W.D.= 3.90mm	○	○
	LPL 80× / 0.80(S) W.D.= 0.85mm	○	○
	LPL 100× / 0.90(S) W.D.= 1.00mm	○	○
Metallurgical LWD Infinity Plan Objectives for Bright & Dark Field	M PLAN 5× / 0.13 BD W.D.=24.23mm		•
	M PLAN 10× / 0.25 BD W.D.= 18.48mm		•
	M PLAN 20× / 0.40 BD W.D.= 8.35mm		•
	M PLAN 50× / 0.70 BD W.D.= 1.95mm		•
	M PLAN 80× / 0.80 BD W.D.= 0.85mm		○
Seidentopf Trinocular Head	Inclined 30°, interpupillary distance: 48-76mm Light distribution (both):100: 0 (100% for eyepiece) 80:20 (80% for trinocular head,and 20% for eyepiece)	•	•
Nosepiece	Quintuple	•	
	Quadplex (specially for bright /dark field objectives)		•
Mechanical Stage	Three layers, Stage size: 210 mm×180mm, Moving range:50×50mm , Scale : 0.1mm	•	•
Coaxial Coarse and Fine Focusing unit	Coarse stroke: 10mm, Fine stroke per rotation: 0.2mm, fine division 2 μm.	•	•
Polarizing Unit	Polarizer /Analyzer	•	•
Illumination	12V/50W Halogen (Input voltage: 100V~240V)	•	•
Filter	Blue	•	•
	Green	○	○
	Amber	○	○
	Grey	○	○
C-mount	1× C-Mount	○	○
	0.5× C-Mount (focus adjustable)	○	○
Adaptor for Digital Photograph	Use for CANON / NIKON / OLYMPUS etc.	○	○
Note: "•"In Table Is Standard outfits, "○" Is Optional Accessories.			
Packing Size: 660mm×590mm×325mm		Gross Weight: 17 kgs	Net Weight: 12.5 kgs



Analyzer & Polarizer for simple polarizing observation

Objective specification: ("●" Is Standard outfits, "○" Is Optional Accessories.)

	Objective	N.A.	Working Distance (mm)	RIM-10	RIM-10D
Metallurgical LWD Infinity Plan Objectives	LPL 5×	0.13	24.23	●	
	LPL 10×	0.25	18.48	●	
	LPL 20×	0.40	8.35	●	
	LPL 40×	0.65	3.90	○	
	LPL 50×	0.70	1.95	●	
	LPL 80×	0.80	0.85	○	
	LPL 100×	0.90	1.00	○	
Metallurgical LWD Infinity Plan Objectives for Bright/Dark Field	M PLAN 5× BD	0.13	24.23		●
	M PLAN 10× BD	0.25	18.48		●
	M PLAN 20× BD	0.40	8.35		●
	M PLAN 50× BD	0.70	1.95		●
	M PLAN 80× BD	0.80	0.85		○



Metallurgical LWD Infinity Plan Objectives



Metallurgical LWD Infinity Plan Objectives for Bright & Dark Field

Shri Engineering Pvt Ltd

Imperial Heights, LIG-6/503, Kabir Nagar, Ner AIIMS Residency, Raipur, CT(22) 492099, (Vadodara, Chennai and Indore)

Mob: +91 8349 02 0230 | +91 9979 87 8092 **Web:** www.shriengineering.co.in | www.shriengineering.com

Email: ajinkya@shriengineering.com | popat@shriengineering.com | ankita@shriengineering.com