

SALT SPRAY CHAMBER (INNER 40*30*24) INCH (150 LITRE) AS PER ASTM B-117

TECHNICAL SPECIFICATION. (INNER ACRALIC /OUTER BODY S.S: -

Chamber Temperature: Ambient to 45 C.

- Air Saturator Temperature 40o C.
- Fog Collection Funnel: 10 cm Diameter & 80 cm²Area
- pH Value of Salt Solution: 6.5 to 7.2
- Test Air Pressure: 0.7kg/cm² -1.2kg/cm²
- Mass of Salt Addition: 5% of Salt Addition
- INNER BODY MATERIAL: 10MM ACRALIC
- Chamber Temperature Least Count: 0.1 0 C
- Chamber Temperature Repeatability ±20 C
- Air Saturator Temperature Least Count 0.1 0 C
- Air Saturator Temperature Repeatability ±20 C
- Electrical supply: 15 Amp. 230 V AC, Single Phase, 50 Hz + Earth
- Power consumption: 4.2 KW



SHRI ENGINEERING PVT LTD

**Imperial Heights, LIG-6/503, Kabir Nagar, Near AIIMS Residency
Raipur, CT (22) 492099**

Web : www.shriengineering.co.in / www.shriengineering.com

Branch's : Vadodara, Chennai , Indore, Pune & Delhi