



TZM7045T-R3L



TZM7045V-R3L



TZM7045T-T9L

TZM7045 series stereo zoom microscope Provide high-quality, durable and reliable optical system and operating mechanism. Range of accessories, diversified portfolio allocation. Meet the modern biology, medicine, scientific research, modern electronics industry online testing and other technology industries such as high-precision requirements.

	Specification	TZM7045	TZM7045T	TZM7045V
Eyepiece	High eye point wide field eyepiece WF10X/20mm,	●	●	●
	High eye point wide field eyepiece WF15X/15mm,			
	High eye point wide field eyepiece WF20X/10mm			
Observation head	Binocular head . 45 ° tilt , 360 ° rotation ; 0.70X ~ 4.5X continuous zoom lens . Long working distance 100mm. Interpupillary distance adjustment range 54-75mm; two eyepiece diopter can be adjusted to regulate the range of ± 5	●		
	Trinocular viewing head . 45 ° tilt , 360 ° rotation ; photographic camera can be equipped with the interface ; 0.70x ~ 4.5x continuous zoom lens . Long working distance 100mm. Interpupillary distance adjustment range 54-75mm; two eyepiece diopter can be adjusted to regulate the range of ± 5 diopter.		●	
	Trinocular viewing head . 45 ° tilt , 360 ° rotation equipped with photographic camera interface ; 0.70x ~ 4.5x continuous zoom lens . Long working distance 100mm. Interpupillary distance adjustment range 54-75mm; two eyepiece diopter can be adjusted to regulate the range of ± 5 diopter.			●
Auxiliary lens	0.5x/165mm. 1.5x/45mm. 2x/30mm.	○	○	○
Focus brackets	1 focus frames, focusing hand wheel adjustable elastic , lifting range 50mm.	●	●	●
	3 industrial binding Focus Frame			
Base	small flat base			
	transmission base , the upper and lower light source is a halogen lamp 12V15W (adjustable brightness), (7W fluorescent optional)			
	3 large flat base			
	5 vertical arm large flat base			
	B6 Column oblique flat base			
	fan base			
	2 arm stand fan base			
	3L stand arm -in LED light base, the upper and lower LED lighting , independent switch , adjustable brightness , low security , low power consumption , low heat , long life.	●	●	●
	4L stand arm -in LED light base, the upper and lower LED lighting , independent switch , adjustable brightness , low security , low power consumption , low heat , long life.			
	TTL1 arm Column Stand			
TTL2 arms Column Stand				
Ring light / LED light / fiber optic lighting	○	○	○	
Other optional	Variety of other base, moving platform, ring lights , fluorescent lights, fiber optic lighting, etc.	○	○	○

The Specifications are subject to change. '●' Standard Supply , '○' Optional